

PASCOL® Easy-Prep Wood Primer

Page 1 of 2
Resource Code 3456 - Line
November 2009

DESCRIPTION

- Pascol Easy-Prep Wood Primer is an oil based primer that penetrates and protects bare timber. With maximum filling, bridging and sealing properties, it provides an excellent base for oil based undercoats and Trim enamel finishing coats.

PRINCIPAL CHARACTERISTICS

- Suitable for exterior use only.
- Maximum filling, bridging & sealing
- Protects bare timber
- Penetrates timber
- Blocks tannin stains
- Turps clean up

COLOURS AND GLOSS

- Colour – Pink / White

BASIC DATA

- **Surface Dry** Six (6) hours.
- **Recoat** Twenty four (24) hours.
- **Fully Cured** Seven (7) days.
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** Up to 14 m²/L (depending on the texture, surface porosity and method of application).
- **Wet Film Thickness** 71 microns
- **Dry Film Thickness** 40 microns
- **Thinning** Up to 5% mineral turps, if necessary.
- **Clean up** Thoroughly clean equipment with mineral turps away from drains.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Ensure surface is clean and dry, and free from dust, dirt and grease. All loose, peeling or flaking material must be removed. Uneven surfaces should be sanded smooth with fine abrasive paper and all dust removed.
- Sand enamel painted surfaces until all gloss is removed.
- Holes and cracks in exterior timber and glazing rebates should be primed with Pascol Easy-Prep Wood Primer before being filled with an exterior grade timber putty.
- If mould is present, clean surface with household bleach then rinse well with clean water.
- Test soundness of previously painted surfaces by cutting a small X in the paint with a sharp blade. Stick a piece of tape firmly over the X and pull off. If the paint pulls away, the surface is unsound. Repeat at random in a number of areas. Unsound surfaces should be stripped for best results.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.
- **Bare timber and hardboard:** Apply one coat of Pascol Easy-Prep Wood Primer to correctly prepared surface. One coat of Pascol Easy-Prep All Purpose Undercoat should be applied if finishing with an oil based system.
- **Surfaces previously painted with water or oil based paint:** Spot prime any correctly prepared bare timber areas with Pascol Easy-Prep Wood Primer.
- **Interior bare MDF:** Apply one coat of Pascol Easy-Prep Primer Sealer Undercoat to correctly prepared surface.

INSTRUCTIONS FOR USE

- Stir well before and during use with a broad paddle.
- If desired, thin sparingly with mineral turps.
- Do not apply when temperature is below 10°C or above 35°C or when humidity is very high.
- Apply one full even coat by brush or roller. Use a quality brush or roller. Brush well into cracks, nail holes, joints and end grain.

SAFETY DATA

- **Caution** Flammable
Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 1 and 4 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- Approved to APAS 0181.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.
3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.
4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.