

Pascol® Trim Water Based Enamel

Page 1 of 2
Resource Code 3468 - Line
November 2009

DESCRIPTION

Pascol Trim Water Based Enamel is hardwearing and provides a smooth finish. Use on interior and exterior trim, woodwork, skirting boards, window frames and sills, furniture and walls in wet areas. Today's water based enamels are as tough and durable as traditional oil based enamels in most painting situations. Using water based enamel offers the added benefit of low odour, non yellowing and fast drying compared to traditional oil based enamels including being better for the environment. Not suitable for surfaces that come into contact with hot objects like kitchen benchtops.

PRINCIPAL CHARACTERISTICS

- Suitable for interior and exterior use.
- For doors, windows and trim.
- Hard wearing smooth finish.
- Non-yellowing.
- Fast drying.
- Low odour.
- Clean up in water

COLOURS AND GLOSS

- Bases may be tinted as required. Refer to the PASCOL® Colour Card. May also be tinted to most colours in the Wattyl Colour Designer colour range or other competitor colour ranges through the Wattyl tinting system.
- Gloss and Satin

BASIC DATA

- **Surface Dry** Thirty (30) minutes.
- **Recoat** 2-3 hours.
- **Fully Cured** Seven (7) days.
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** Up to 14 m²/L (depending on the surface porosity and method of application)
- **Wet Film Thickness** 72 microns
- **Dry Film Thickness** 18 microns
- **Thinning** Thin with up to 5% water, if required.
- **Clean up** Thoroughly clean equipment with water.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- For use on suitably prepared timber, brick, cement render, paper-faced plasterboard, plaster and previously painted surfaces.
- Ensure surface is clean, dry and free from dust, dirt and grease. All loose, peeling or flaking material must be removed.
- Sand the surface smooth and remove all dust. Sand enamel painted surfaces to remove gloss.
- Fill holes and cracks with a suitable filler and sand lightly to an even finish.
- If mould is present, clean surface with household bleach then rinse well with clean water.
- **Previously painted surfaces – water based and preprimed MDF:** No undercoat required on correctly prepared sound surfaces. Apply one coat of Pascol Easy-Prep Primer Sealer Undercoat where required to create an even base over patched or damaged surfaces, or to maximise opacity of finish coat.
- **Previously painted surfaces – oil based:** Apply one coat of Pascol Easy-Prep Primer Sealer Undercoat to correctly prepared surface.
- **New interior timber & MDF:** Apply one coat of Pascol Easy-Prep Primer Sealer Undercoat to correctly prepared surface.
- **New exterior and tannin rich timbers:** Apply one coat of Pascol Easy-Prep Primer Sealer Undercoat or Pascol Easy-Prep Wood Primer to correctly prepared surface.
- **Wallboard/paper-faced plasterboard:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surface.
- **Bare cement render, brick, fibre cement, masonry:** Apply one coat of Pascol Easy-Prep Primer Sealer Undercoat or Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surface.
- **New plaster surfaces, fibrous plaster:** Apply one coat of Pascol Uniseal or Wattyl Master Prep Pigmented Sealer to correctly prepared surface.

- **Ferrous metals:** Apply two coats of Killrust Heavy Duty Metal Primer or Wattyl Master Prep Metal Primer according to directions.
- **Non-ferrous metals:** Apply one coat of Killrust Etch Primer or Wattyl Aqua Prep Galvanised Iron Primer according to directions.
- For specific substrate preparation, see relevant specification sheets.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.
- Not suitable for areas subject to cleaning with harsh cleaning agents.

INSTRUCTIONS FOR USE

- Stir well before and during use with a broad paddle. If desired, thin sparingly with water.
- Apply two full coats with brush, roller or spray.
- Use short nap (6-9mm) synthetic roller or quality synthetic brush. Moisten brushes or rollers before use and keep them working freely. Rinse occasionally in clean water. Spread the paint quickly to an even film over a small section, laying off lightly into freshly painted sections. Avoid applying excessively thick coats as running or sagging may occur.
- Splashes should be removed immediately with a damp cloth. For best results to achieve a smoother finish, lightly sand after undercoating and between finishing coats with 240 or finer abrasive paper and remove dust.

SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- White available in, 1, 2, and 4 litre containers, bases in 2 litre size only.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.