

PASCOL DECKING OIL

Page 1 of 2
Resource Code 346151
November 2010

DESCRIPTION

- Pascol Decking Oil is an easy to use penetrating oil designed to protect and enhance the natural beauty of exterior timber decking. It has been formulated to highlight the timber grain and produce a natural timber-look finish.
- Pascol Decking Oil contains fungicide to provide protection against discolouration caused by mould growth. It also contains wax for improved water repellency and durability.

PRINCIPAL CHARACTERISTICS

- For use on Timber Decks, Outdoor Furniture, Screens & Fences
- Penetrating oil
- Nourishes timber
- Resists mould & fungus
- Easy to apply
- Easy to maintain
- Suitable for exterior use only.

COLOURS AND GLOSS

- Natural tone to enhance timber colours
- Subdued gloss

BASIC DATA

- **Touch Dry** 4-8 hours
- **Recoat** 24 hours.
- **Dry Time** Allow minimum 16 hours drying before subjecting to light foot traffic; ensure stained outdoor furniture is dry before using.
All figures are quoted at 25 °C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity. Drying may take longer over less porous or previously oiled, stained or sealed timber. Drying may take longer on tannin rich timbers due to varying timber compositions.
Do not apply if rain or dew is likely within 16 hours.
- **Coverage per coat** up to 6-10 m²/L per coat. Varies depending on the texture and porosity of the timber.
- **Thinning** Not recommended
- **Clean up** Thoroughly clean equipment with mineral turps away from drains. Soak all used cloths and sanding dust in water after use as they could self ignite.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Suitable for use on exterior bare timber including Cedar, Oregon, Redwood, Treated Pine, Tallowwood, Brushbox, Merbau and Jarrah; or over similar weathered oil or stain finishes.
- Ideal for timber decks, outdoor furniture screens and fences etc
- Not suitable for previously painted or varnished timber unless it is sanded back to bare.
- Not suitable for use on non-timber surfaces.
- Application should not be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process. Do not apply when rain or dew is likely within 16 hours.

New Timber

- Allow resinous timbers such as Merbau, Tallow wood, Jarrah, Blackbutt and Cypress Pine to weather for 4-6 weeks prior to coating. To assist with the removal of resinous materials, rinse with water several times during this period. Use galvanised or stainless steel fasteners to avoid rust stains.

Previously Oiled or Stained Timber

- Previously oiled or stained decks in sound condition may be re-oiled to rejuvenate following suitable cleaning and preparation. If a more transparent, new looking appearance is required, sand timber back to bare before applying oil.
- Previously oiled decks where the oil is very patchy, or in unsound condition, should be stripped to bare timber before applying oil.

Previously Coated Timber

- Non-compatible coatings such as paints and varnishes must be completely removed to bare timber before applying Pascol Decking Oil.

All Timbers

1. To remove previous coatings, punch nail heads below the surface before coarse sanding (40-80 grit) all surfaces and edges. Smooth sand (120-240 grit) and remove all dust.
2. Ensure all surfaces to be coated are free from any mould, wax, grease, oil or dirt.
3. Clean surfaces thoroughly using Watty! Weathergard Decking Cleaner.
4. If mould is present, remove as much as possible by scraping or brushing. Clean remaining area with household bleach and water.
5. Rinse entire surface with clean water and allow to dry.

INSTRUCTIONS FOR USE

- Stir well with a wide flat stirrer before and regularly during use.
- Apply two coats with a clean, dry, good quality paint brush, flat applicator pad or spray gun.
- To avoid lap-marks apply Pascol Decking Oil along the full lengths of timber, working your way across the deck.
- Apply first coat, paying particular attention to exposed edges and end grain. Once timber is fully saturated, wipe off excess if any and allow to dry overnight.
- Apply second coat, allow to dry for 30 minutes, wipe off excess and allow to dry for a further 24 hours before subjecting to light traffic.
- When applied to timber furniture, ensure coated timber is dry before use.

MAINTENANCE

Exterior timber oils require regular maintenance. As a guide we recommend re-coating the surface every 3-9 months or as soon as timber shows signs of weathering. Due to high timber density, some new hardwood surfaces may require an early initial maintenance before normal durability is established.

SAFETY DATA

- **Caution** Hazardous Substance according to the criteria of NOHSC.
- Flammable
- Provide adequate ventilation during use.
- Soak all used cloths in water after use as they may self ignite.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**
- If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre.
- Phone 131126 (Australia).
- If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
- If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
- If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 6 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Watty! Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Watty! products. Watty! recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty!; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
2. The information in this technical data sheet was prepared using information gathered during product development. While Watty! endeavours to update this information and maintain the accuracy and currency of its contents, Watty! cannot guarantee that the information provided is wholly comprehensive.
3. Watty! recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Watty! Office.
4. To the full extent permitted by law, Watty!'s liability for breach of a condition or warranty implied into the contract for sale between Watty! and you by law is limited at Watty!'s election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.