

# Pascal Colour Change Ceiling White

Page 1 of 2  
Resource Code 352214  
September 2011

## DESCRIPTION

Pascal Colour Change Ceiling Paint is specifically formulated with colour change technology to apply purple and dry white, to ensure consistent paint coverage on ceilings with no more missed spots. With low spatter it is easy to use with less mess.

## PRINCIPAL CHARACTERISTICS

- Suitable for use on interior ceilings only
- Colour change technology shows assists missing spots on ceilings.
- Flat finish helps hide surface imperfections.
- For ceilings in wet areas use Pascal Kitchen & Bathroom Ceiling Paint.

## COLOURS AND GLOSS

- Colour - white
- Flat

## BASIC DATA

- **Surface Dry** Thirty (30) minutes
- **Recoat** Two (2) hours
- **Fully Cured** Seven (7) days  
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** up to 16 M<sup>2</sup>/L (depending on the texture, surface porosity and method of application)
- **Wet Film Thickness** 63 microns
- **Dry Film Thickness** 16 microns
- **Thinning** If required, thin sparingly with water.
- **Clean up** Thoroughly clean equipment with water away from drains.

## RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- For use on suitably prepared paperfaced plasterboard and previously painted interior ceilings. The colour change technology assists in obtaining an even finish on difficult to paint areas with shadows, poor light and high ceilings.
- **Not recommended** for use on walls, wet areas or exterior applications. Ceilings in wet areas are best coated using Pascal Kitchen & Bathroom Ceiling Paint.
- Do not apply in areas adjacent to tiles as grout can prevent purple colour from fading.
- Ensure surface is clean, dry and free from dust, dirt and grease. All loose, peeling or flaking material must be removed.
- Sand the surface smooth and remove all dust. Sand enamel painted surfaces to remove gloss.
- Fill holes and cracks with a suitable filler and sand lightly to an even finish.
- If mould is present, clean surface with household bleach then rinse well with clean water before painting.
- **Previously painted surfaces – water based:** No undercoat required on correctly prepared sound water based surfaces. Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat where required to create an even base over patched or damaged surfaces, or to maximise opacity of finish coat.
- **Previously painted surfaces - oil based:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surface.
- **Bare Timber & MDF:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared timber. On tannin rich timbers apply one coat of Pascol Easy-Prep Wood Primer or Primer Sealer Undercoat.
- **Bare cement render, brick, fibre cement, masonry:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surface.
- **New paper-faced plasterboard:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surface.
- **New Plaster Surfaces:** Apply one coat of Wattyl Master Prep Pigmented Sealer to correctly prepared surface.
- For specific substrate preparation, see relevant specification sheets.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

### INSTRUCTIONS FOR USE

- Stir contents thoroughly with a broad paddle before and during use.
- Apply two even coats to a correctly prepared surface by brush, roller or spray equipment using the initial purple colour as a guide.
- Do not touch up areas once the paint has started to dry.
- May appear patchy whilst drying but will dry to an even, white finish.

### SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**  
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).  
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.  
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.  
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

### ADDITIONAL DATA

- Available in 1, 2, 4, and 10 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- The use of alkaline cleaners may result in temporary reappearance of the purple colour.
- For further information, contact the Watty! Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Watty! products. Watty! recommends that:  
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty!; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Watty! endeavours to update this information and maintain the accuracy and currency of its contents, Watty! cannot guarantee that the information provided is wholly comprehensive.

3. Watty! recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Watty! Office.

4. To the full extent permitted by law, Watty!'s liability for breach of a condition or warranty implied into the contract for sale between Watty! and you by law is limited at Watty!'s election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.