

PASCOL® Ceiling Paint

Page 1 of 2
Resource Code 347905
December 2009

DESCRIPTION

- Pascol Ceiling Paint is suitable for any living and bedroom area. With low spatter technology it is easy to use with less mess. It has added protection against bacteria and the growth of mould, mildew and fungus providing the benefits of lasting assurance for active living. With low odour and low ammonia, Pascol Ceiling Paint is gentler on your senses and better for your environment. For ceilings in wet or damp areas use Living and Bedroom paint.

PRINCIPAL CHARACTERISTICS

- Flat finish hides surface imperfections
- Good coverage
- Resists bacteria & mould
- Low odour & ammonia
- Low roller spatter
- Clean up in water
- Interior use only

COLOURS AND GLOSS

- Colour - White
- Gloss Level - Flat

BASIC DATA

- **Touch Dry** Thirty (30) minutes
- **Recoat** Two (2) hours
- **Fully cured** Seven (7) days
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** Up to 16 m²/L (depending on the texture, surface porosity and method of application)
- **Wet Film Thickness** 63 microns
- **Dry Film Thickness** 16 microns
- **Thinning** If required, thin sparingly with water.
- **Clean up** Thoroughly clean equipment with water.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- For use on suitably prepared timber, MDF, brick, cement render, fibre-cement, masonry, paper-faced plasterboard, plaster and previously painted surfaces.
- Ensure surface is clean, dry and free from dust, dirt and grease. All loose, peeling or flaking material must be removed.
- Sand the surface smooth and remove all dust. Sand enamel painted surfaces to remove gloss.
- Fill holes and cracks with a suitable filler and sand lightly to an even finish.
- If mould is present clean the surface with household bleach then rinse well with clean water.
- **Previously painted surfaces:** No undercoat required on correctly prepared sound water-based surfaces. Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat where required to create an even base over patched or damaged surfaces, or to maximise opacity of the finished coat.
- **Previously painted surfaces - oil based:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surfaces.
- **Bare Timber & MDF:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared timber. On tannin-rich timbers apply one coat of Pascol Easy-Prep Wood Primer or Primer Sealer Undercoat.
- **Bare cement render, brick, fibre cement, masonry:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surfaces.
- **New paper-faced plasterboard:** Apply one coat of Pascol Easy-Prep Acrylic Sealer Undercoat to correctly prepared surfaces.
- **New Plaster Surfaces:** Apply one coat of Pascol Uniseal or Watty Master-Prep Pigmented Sealer to correctly prepared surfaces.

- For specific substrate preparation, see relevant specification sheets.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.
- Not suitable for areas subject to cleaning with harsh cleaning agents.

INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply two full even coats to a correctly prepared surface by brush, roller or spray equipment.
- For best results when rolling, use a 12mm pile synthetic roller on smooth and semi-smooth surfaces. Longer nap synthetic rollers may be used on rough surfaces.
- Ensure brushes and rollers are only slightly damp with water before use.
- Cover brushes and rollers and trays with plastic during working breaks. Keep lid on cans at all times when not in use.

SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S** A Material Safety Data Sheet (M.S.D.S) is available on request.
- **First Aid**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 2, 4, 6, 10, 15 litres.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- Avoid exposure to excessive steam or condensation for 48 hours after application of the final coat.
- For further information, contact the Wattyl Information Hotline. Phone 132-101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.
3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.
4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited to Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.