

PASCOL® Kitchen & Bathroom Semi Gloss

Page 1 of 2
Resource Code 3476 & 3522 - Lines
September 2011

DESCRIPTION

Pascal Kitchen & Bathroom Paint is suitable for areas that are exposed to moisture or where an ultra hard wearing scrubbable finish is required. This premium acrylic formulation provides the added protection against bacteria and the growth of mould, mildew and fungus giving lasting assurance for active living. With low odour and low ammonia it is gentler on the senses and better for your environment. For lower gloss ceilings in wet areas use Kitchen & Bathroom Ceiling Paint.

PRINCIPAL CHARACTERISTICS

- Suitable for interior use only.
- For kitchens, bathrooms, laundries and wet areas.
- Easy to clean.
- Resists mould, mildew & fungus.
- Low odour better for your environment.
- Stain resistant.
- Clean up in water.

COLOURS AND GLOSS

- Bases may be tinted as required. Refer to the PASCOL® Colour Card. May also be tinted to most colours in the Watty Colour Designer colour range or other competitor colour ranges through the Watty tinting system.
- Semi Gloss.

BASIC DATA

- **Touch Dry** One (1) hour
 - **Recoat** Two (2) hours
 - **Fully Cured** Seven (7) days
- All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** Up to 16 m²/L (depending on the surface porosity and method of application)
 - **Wet Film Thickness** 63 microns
 - **Dry Film Thickness** 23 microns
 - **Thinning** If required, thin with up to 5% water.
 - **Clean up** Thoroughly clean equipment with water.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- For use on suitably prepared timber, brick, cement render, paper-faced plasterboard, plaster and previously painted surfaces.
- Ensure surface is clean, dry and free from dust, dirt and grease. All loose, peeling or flaking material must be removed.
- Sand the surface smooth and remove all dust. Sand enamel painted surfaces to remove gloss.
- Fill holes and cracks with a suitable filler and sand lightly to an even finish.
- If mould is present, clean surface with household bleach then rinse well with clean water.
- **Previously painted surfaces:** No undercoat required on correctly prepared sound water based surfaces. Apply one coat of Pascal Easy-Prep Acrylic Sealer Undercoat where required to create an even base over patched or damaged surfaces, or to maximise opacity of finish coat.
- **Previously painted surfaces - oil based:** Apply one coat of Pascal Easy-Prep Acrylic Sealer Undercoat to correctly prepared surface.
- **Bare Timber & MDF:** Apply one coat of Pascal Easy-Prep Acrylic Sealer Undercoat to correctly prepared timber. On tannin rich timbers apply one coat of Pascal Easy-Prep Wood Primer or Primer Sealer Undercoat.
- **Bare cement render, brick, fibre cement:** Apply one coat of Pascal Easy-Prep Acrylic Sealer cement, masonry Undercoat to correctly prepared surface.
- **New paper-faced plasterboard:** Apply one coat of Pascal Easy-Prep Acrylic Sealer Undercoat to correctly prepared surface.
- **New Plaster Surfaces:** Apply one coat of Watty Master Prep Pigmented Sealer to correctly prepared surface.

- For specific substrate preparation, see relevant specification sheets.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.
- Not suitable for areas subject to cleaning with harsh cleaning agents.

INSTRUCTIONS FOR USE

- Stir well before and during use with a broad paddle.
- Apply two coats to a correctly prepared surface by brush, roller or spray equipment.
- For best results when rolling, use a 12mm pile synthetic roller on smooth and semi-smooth surfaces. Longer nap synthetic rollers may be used on rough surfaces.
- Ensure brushes and rollers are only slightly damp with water before use.
- When airless spraying, use a 13-15 thou spray tip.
- Cover brushes, rollers and trays with plastic during work breaks.
- Keep lid on cans

SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.

SAFETY DATA - Continued

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 1 and 4 litres. White also available in 2, 6, 10 and 15 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- Leave seven days after application of final coat before washing.
- When subject to steam or condensation, water based paints may develop a stain, which can be removed with a damp cloth. Avoid exposure to excessive steam or condensation for 48 hours after application of the final coat.
- Approved to APAS 0260/2, AS3730.2
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:

(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.